



Tyvek.

DUPONT™ TYVEK® STRAIGHTFLASH™ VF



DuPont™ StraightFlash™ VF ties the window or door frame directly to the sheathing or water-resistant barrier to protect from bulk water leaks.

An innovative dual-sided flashing material that integrates brick mold, non-integral flanged and non-flanged windows and doors with the building envelope.

DuPont™ StraightFlash™ VF (Versatile Flange) is an innovative, dual-sided self-adhered flashing material that provides a reliable moisture seal to integrate brick mold, non-integral flanged and non-flanged windows and doors with the building envelope. The unique dual-sided adhesive and specially designed release papers allow this flashing to tie the window or door frame directly to the sheathing or water-resistant barrier to protect from bulk water leaks providing superior protection against the elements.

When used as part of the DuPont Weatherization System, DuPont™ StraightFlash™ VF also helps contribute towards

U.S. Green Building Council LEED® points, LEED® for Homes points, and The National Green Building Standard™, as well as helping to create more sustainable, durable structures.

BENEFITS

Superior protection from water damage

- 100% butyl sealant provides excellent adhesion to most common building materials
- Meets the AAMA 711-13 material standard at the highest classification levels: Class A (no primer) and Level 3 Thermal Exposure (80°C / 176°F for 7 days)
- Meets and Exceeds ASTM E331 Standard Test Method for Water Penetration of Exterior Windows, Skylights, Doors, and Curtain Walls by Uniform Static Air Pressure Difference: no leakage at 300 Pa (equivalent to 50 mph windload), even after thermal aging (0-120°F)
- Does not contain asphaltic / bitumen adhesive materials which many window manufacturers prohibit due to adverse material reactions, such as black staining, oozing, and deformation over time, particularly with vinyl flanges.
- Can be installed at external temperatures as low as -4°C (25°F) as long as the surface is clean and free from frost and ice

Easy installation

- Features unique dual-sided adhesive and quick-release, scored backing
- Forgiving initial tack provides ability to correct installation mistakes
- Packaged in ready-to-use 6" x 125 ft rolls in an easy dispensing carton

Superior durability

- Constructed with a durable, micro-creped DuPont™ Tyvek® top-sheet, a 100% butyl adhesive layer, and a specially designed, scored release liner
- Designed to withstand up to 270 days of UV exposure
- Tough, tear-resistant

Excellent adhesion performance

- 100% butyl adhesive performs through extreme temperatures
- Adheres to most common building materials



DUPONT™ STRAIGHTFLASH™ VF

THE DUPONT™ BUILDING KNOWLEDGE CENTER

All DuPont building envelope systems products are backed by industry-leading building science and unrivaled industry support provided by The DuPont™ Building Knowledge Center, your source for the DuPont product information and technical support you need to build quality, durable and energy-efficient structures.

DUPONT™ TYVEK® SPECIALIST NETWORK

A national group of highly trained field representatives is available to assist you with your installations. From the latest updates on building codes, to keeping up with current trends and challenges, your local DuPont™ Tyvek® Specialist can provide on-site consulting and training to help you make sure the job gets done right.



LIMITED WARRANTY

DuPont™ StraightFlash™ VF is backed by a limited warranty. For more information please visit www.weatherization.tyvek.com or call 1-800-44-Tyvek.

DUPONT™ TYVEK® CERTIFIED INSTALLERS

The DuPont™ Tyvek® Certified Installer Network is one more way to put the building science expertise of DuPont right at your fingertips. Your DuPont™ Tyvek® Certified Installer provides trained installation services for DuPont Weatherization Products to help seal the building envelope. To locate a certified installer in your area, please visit www.weatherization.tyvek.com.

For more information please visit
www.weatherization.tyvek.com
or call 1-800-44-Tyvek

COMPLETE SYSTEM OF PRODUCTS

For optimal protection on all your building projects, use DuPont™ StraightFlash™ VF with the complete line of DuPont building envelope systems products, including:

- DuPont™ Tyvek® HomeWrap®
- DuPont™ Tyvek® StuccoWrap®
- DuPont™ Tyvek® DrainWrap™
- DuPont™ Tyvek® ThermaWrap™ R5.0
- DuPont™ Tyvek® ThermaWrap™ LE
- DuPont™ RoofLiner
- DuPont™ FlexWrap™ NF
- DuPont™ StraightFlash™
- DuPont™ Flashing Tape
- DuPont™ Tyvek® Tape
- DuPont™ Residential Sealant
- DuPont™ Tyvek® Wrap Caps
- DuPont™ Adhesive/Primer
- DuPont™ Window & Door Foam
- DuPont™ RainVent™ Battens



Innovative, dual-sided self-adhered flashing material.



Proud Member